

## key features & benefits

- ▼ Efficient & powerful 4.25 HP, AC NextGEN III Eco-Drive System™ (NEMA IE3 Premium Efficiency)



- ▼ Intuitive LED with dual speed and incline toggle controls, audio input, speakers, USB port, reading rack/tablet holder and cup holders



- ▼ Simple design makes the 6000 treadmill easier and more efficient to assemble, service and relocate
- ▼ Contact and wireless heart-rate sensors are compatible with a variety of industry-leading monitors
- ▼ Low step-on height and rubber foot grips with durable full-commercial components on a space-saving commercial frame
- ▼ 60" x 20" Siegling premium lubricant-infused running belt with 1" reversible phenolic deck provides long lasting reliability



- ▼ More than 20 exercise programs and integrated 2-speed personal fan
- ▼ Illuminated power-on switch with quick-connect safety clip
- ▼ The Smooth Deck Shock Absorption System with urethane suspension delivers a stable and flexible running surface designed to provide the ultimate comfort, reducing stress on knees and joints
- ▼ Zinc-dipped anti-corrosion coating for superior rust protection

**circle**  
FITNESS



OUR MOST  
**EFFICIENT**  
TREADMILL EVER!

## M6 IE3 TREADMILL CIR-TM6000IE3-C

**innovative**  
FITNESS

The M6 IE3 treadmill features the NEMA IE3 Premium Efficiency Motor – the most efficient treadmill motor available – without compromising power. Paired with high-quality full commercial components on a space-saving frame, this treadmill is built for unparalleled durability, efficiency and comfort.



### technical specs

**Product Weight:** 302 lbs.

**Running Surface:** 60" x 20"

**Width:** 36"

**Length:** 78"

**Height:** 57"

**Motor:** 4.25 HP, AC NextGEN III Eco-Drive™ NEMA Premium IE3

**Electrical:** 120V, 20 amp dedicated NEMA 5-20

**Certification:** UL, CSA, CE & EU MEPS

**Rollers:** 2.75"

**Step Up Height:** 7"

**Belt:** Siegling premium with Texglide™ technology

**Deck:** 60" x 20" running surface, with 1" reversible phenolic deck

**Suspension:** Smooth Deck Shock Absorption System with urethane suspension

**Speed Range:** 0.2 - 15.5 MPH

**Incline Range:** 0 - 15% incline

**User Weight:** 450 lbs.

**Transport Wheels:** Easy-to-move with front-mounted dual wheels without elevating

**Frame:** Zinc-dipped, anti-corrosion coated heavy gauge steel

**Heart Rate Receiver:** Contact & telemetric heart-rate sensors

**Display:** 8 x 16 dot matrix console with message window + HR status bar

**Display Feedback:** Time, distance, heart-rate, calories, speed, incline, calories/hour, pace

**Programs:** 20 programs, 1 target, 3 HRC, 1 fitness test, 2 custom

**Keypad:** Teflon keypad TPU lasts 25% longer than PVC

**Standard Features:** Hand pulse, fan, heart-rate receiver chest belt compatible, 4 quick keys for both speed & incline & reading rack/tablet holder

**Warranty:** 10 years frame, 6 years motors & parts, 2 years wearable items, 1 year labor in light commercial applications, including hospitality, multi-family, fire/police, municipality, corporate & junior/senior high schools (under 8 hours of daily use)